

## DECOR DESIGNER

### T Bar Recessed Emergency Light

The Decor DS series provides a self-contained emergency lighting fixture for recessing into suspended grid or lay-in ceiling systems. By recessing into the ceiling the DS series provides a clean and unobtrusive emergency light to blend with your chosen Decor.

#### Construction

- One piece, steel housing drops into ceiling T-bar grid and provides cut ceiling tile support. T-bar retaining brackets are included together with provision for chain or cable suspension
- Sturdy 20 gauge steel cabinet with multiple knock-out entries, finished in a durable white powder coat finish (other colors available to order)
- Removable side access panel for ease of service and installation

#### Electrical

- Choice of maintenance free sealed Lead Calcium or Nickel Cadmium batteries
- Brownout sensing assures emergency operation during periods of low line voltage
- Premium, fully automatic current limited "Pulse Switching" charger provides ideal charge conditions for optimum battery performance and life
- Short Circuit battery protection
- Field selectable 120 or 277 VAC input
- Momentary test switch and dual diagnostic LED indicator displays AC presence and Hi-Charge status
- Line-latch prevents unnecessary discharge of battery during installation, loads will not illuminate until after application of utility power
- Low voltage cut-off prevents battery damage and ensures positive charge acceptance following an extended discharge
- Self-Test / Self-Diagnostic monitoring available

#### ORDERING GUIDE – DS Series

Model	Operating Voltage/Wattage				No. of Lighthoods	Lamp Options	Options
DS	Lead Calcium Battery 90 Minute Capacity		Nickel Cadmium Battery 90 Minute Capacity		2 Double Lighting Heads	W69 6V 9W Tungsten Standard W129 12V 9W Tungsten Standard	SD Self-Test/Self-Diagnostic TD 15 Minute Time Delay (Specify AC Voltage) VM Volt Meter B Black Housing and Heads
	2E18	6 Volt – 18 Watts	2N42	6 Volt – 42 Watts	0 No Lighting Heads	L65 6V 5W LED PAR 18 Thermoplastic	
	2E60	6 Volt – 60 Watts	2N90	6 Volt – 90 Watts		L67 6V 7W LED PAR 18 Thermoplastic	
	2E72	6 Volt – 72 Watts				L125 12V 5W LED PAR 18 Thermoplastic	
	4E27	12 Volt – 27 Watts	4N42	12 Volt – 42 Watts		L127 12V 7W LED PAR 18 Thermoplastic	
	4E36	12 Volt – 36 Watts	4N90	12 Volt – 90 Watts			
	4E60	12 Volt – 60 Watts					
	4E72	12 Volt – 72 Watts					
	DS						


Fill in fields from categories above and complete type and part number.

Type Number:

Full Part Number:

Shown with optional LED lampheads

Optional MR16 Heads Available Lamps	
Voltage/Wattage	Lumens
6V 5WLED	300
6V 7WLED	382
12V 5WLED	300
12V 7WLED	382



#### Illumination

- Available with two fully adjustable Par36 or the smaller Par18 lamp heads with a variety of lamp types and wattage's
- Standard lamp is 9 watt
- High capacity units provide for additional remote lighting

#### Certification

- Listed to UL 924, meets NFPA 101 Life Safety Code, NFPA 70-NEC and OSHA requirements



#### Warranty

- 3 Year Limited Warranty

Example: DS2E18-2-L67-SD